

# DIESEL 10PPM

Property	Unit	Minimum	Maximum	Test method	
Appearance at loading temperature	Visual	Clear / Bright Haze rating ≤ 1		ASTM D4176	
Cetane number	-	51,0	-	EN ISO 5165	
Cetane index	-	46,0	-	EN ISO 4264	
Density at 15 °C	kg/m <sup>3</sup>	820,0	845,0	EN ISO 3675	
Polycyclic aromatic compounds	% m/m	-	8,0	EN ISO 12916	
Sulfur content	mg/kg	-	10,0	EN ISO 20846	
Manganese content	mg/l	-	2,0	EN 16576	
Flash Point	°C	>55	-	EN ISO 22719	
Carbon residue on 10% distillation residue	% m/m	-	0,3	EN ISO 10370	
Ash content	% m/m	-	0,0	EN ISO 6245	
Water content	mg/kg	-	200	EN ISO 12937	
Total contamination	mg/kg	-	24	EN ISO 12662	
Copper strip corrosion (3 hrs. at 50 °C)	Rating	Class 1		EN ISO 2160	
Oxidation stability	g/m <sup>3</sup>	-	25	EN ISO 12205	
	h	20	-	EN 15751	
When FAME content > 2% V/V					
Lubricity, corrected wear scare diameter (wsd 1,4) at 60° C	µm	-	460	EN ISO 12156-1	
Viscosity at 40°C	mm <sup>2</sup> /s	2,0	4,5	EN ISO 3104	
Fatty acid methyl ester (FAME) content	% v/v	-	7,0	EN ISO 14078	
Distillation	% (v/v) recovered at 250 °C	% v/v	-	<65	EN ISO 3405
	% (v/v) recovered at 350 °C	% v/v	85	-	
	95 % (v/v) recovered at	°C	-	360	
CFPP	Summer*	°C	-	-5	EN 116
	Intermediate**	°C	-	-11	
	Winter***	°C	-	-20	
Cloud Point	Summer*	°C	-	4	EN 116
	Intermediate**	°C	-	0	
	Winter***	°C	-	-5	

Specification meets at least NBN EN590 / NEN EN590 / ILNAS EN590

\* Summer: April 1st - September 30th

\*\* Intermediate: October 1st - November 15th / March 1st - March 31st

\*\*\* Winter: November 16th - Februari 28th

Edition: 2021

Version: 4